


STAX^{ECO} MULTI

STAX15W30W-TRI

SAP CODE: 2002130




A versatile and efficient LED floodlight

The STAX ECO MULTI is a versatile and efficient LED Floodlight with switchable colour temperature and dual power making it suitable for a wide range of applications.



Photometric Diagram



Unit: cd
 - C0/180 103.8deg
 - C90/270 95.3deg

KEY INFORMATION

Watts	30W
Input Power	15W / 30W
Lumen Output (p/metre)	(15W) 1720 / 1850 / 1740lm (30W) 2710 / 3180 / 2960lm
Install	Surface Mount
Dimming Options	Non-Dimmable
Fitting Colour	Matte Black
Warranty	3 years
IP Rating	IP66
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approval	IPART LCP 29.5

PHOTOMETRICS

Efficacy	(15W) 115 / 123 / 116lm/W (30W) 90 / 106 / 99lm/W
LED	SMD
CCT	4000 / 5000 / 6000K
Beam Angle	110°

ELECTRICAL

Driver	Integral (DOB)
Supply Input	220-240Va.c. 50/60Hz
Driver Output Voltage	-
Power Factor	>0.9
LED Input Current (nominal)	-
Useful life @Ta25° (L70)	54,000hr

CONSTRUCTION

SDCM	<5
Housing	Die-cast Aluminum
Optics	Glass Lens
Adjustable Angle	N/A
Fixings/Hardware	Mounting bracket
Connection Type	Flex
Total Weight	0.6kg
Dimensions	140x178.5x26mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

ACCESSORIES



STAX90D-BRKT-S