

TRIPROOF

TRIPROOF12-DALI

SAP CODE: 2002252


Tried and trusted design.

TRIPROOF are weatherproof LED battens with a striking robust design and suitability for higher ambient temperatures.

This model features a DALI Dimmable Constant Driver 29-42W.



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 110.1deg
 - C90/270 130.8deg

POWER/LUMEN SETTINGS

POWER	LUMENS	EFFICACY	CCT
40W	4600 lm	115 lm/W	4000K
	4900 lm	123 lm/W	5000K
	4500 lm	114 lm/W	6500K

SPECIFICATIONS

Total Weight:	2.40kg
Dimensions:	1215 x 116 x 74mm
Body Material:	Polycarbonate
Diffuser Material:	Polycarbonate (Opal)
Body colour:	Grey
IP Rating:	IP65
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	<5
Driver:	Integral
Power Connection:	PA14 Terminals
Input:	220-240V, 50/60Hz
Electrical Classification:	Class 1
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-20 to 45°C
Smart:	KASTA Compatible
Dimming:	DALI Dimmable Constant Driver 29-42W

LED DRIVER SPEC

Input:	220-240V, 50/60Hz
Output Current:	700mA
Output Voltage:	25-64V

DIMENSIONS

