

TRIPROOF

TRIPROOF12-EMDD

SAP CODE: 2002253


Tried and trusted design.

TRIPROOF are weatherproof LED battens with a striking robust design and suitability for higher ambient temperatures. HACCP approval makes them the perfect choice for food and beverage manufacturing.

This model is an Emergency version and also features a DALI Dimmable Constant Driver 29-42W.



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 109.2deg
 - C90/270 130.5deg

POWER/LUMEN SETTINGS

POWER	LUMENS	EFFICACY	CCT
40W	4100 lm	97 lm/W	4000K
	4300 lm	107 lm/W	5000K
	4100 lm	97 lm/W	6500K

SPECIFICATIONS

Total Weight:	2.65kg
Dimensions:	1215 x 116 x 74mm
Body Material:	Polycarbonate
Diffuser Material:	Polycarbonate (Opal)
Body colour:	Grey
IP Rating:	IP65
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	5
Driver:	Integral
Power Connection:	PA14 Terminals
Input:	220-240V, 50/60Hz
Electrical Classification:	Class 1
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-20 to 40°C
Smart:	KASTA Compatible
Dimming:	DALI Dimmable Constant Driver 29-42W

EMERGENCY KIT

Battery Type:	LiFeP04 3.2V 4.5Ah
Operation Time:	2 Hours
Recharge Time:	16 Hours
Power:	4.5W
Lumen Output:	520lm, C0/D63, C90/D40

DIMENSIONS

