

# TRIPROOF

## TRIPROOF12-SS

SAP CODE: 2002233


### Tried and trusted design.

TRIPROOF are weatherproof LED battens with a striking robust design and suitability for higher ambient temperatures.

This model is power switchable, tritone selectable, and features an Intellisensor for automatic standby dimming.



### PHOTOMETRIC DIAGRAM



Unit: cd  
 - C0/180 110.0deg  
 - C90/270 110.0deg

### POWER/LUMEN SETTINGS

POWER	LUMENS	EFFICACY	CCT
18W	2200 lm	120 lm/W	4000K
	2300 lm	130 lm/W	5000K
	2200 lm	120 lm/W	6500K
36W	4100 lm	102 lm/W	4000K
	4300 lm	110 lm/W	5000K
	4100 lm	101 lm/W	6500K

### SPECIFICATIONS

<b>Total Weight:</b>	2.40kg
<b>Dimensions:</b>	1215 x 116 x 74mm
<b>Body Material:</b>	Polycarbonate
<b>Diffuser Material:</b>	Polycarbonate (Opal)
<b>Body colour:</b>	Grey
<b>IP Rating:</b>	IP65
<b>IK Rating:</b>	IK08
<b>Beam Angle:</b>	120°
<b>CRI:</b>	>80
<b>SDCM:</b>	<5
<b>Driver:</b>	Integral
<b>Power Connection:</b>	PA14 Terminals
<b>Input:</b>	220-240V, 50/60Hz
<b>Electrical Classification:</b>	Class 1
<b>Power Factor:</b>	>0.9
<b>Protection:</b>	Overload / Short Circuit
<b>Lifespan:</b>	>50,000hrs @Ta25°C (L70)
<b>Operating Ambient Temperature:</b>	-30 to 45°C
<b>Smart:</b>	KASTA Compatible
<b>Dimming:</b>	Non-Dimmable

### INTELLISENSOR

<b>Sensor Type:</b>	Microwave Motion Sensor
<b>Detection Angle:</b>	150°
<b>Mounting Height:</b>	3m          6m (max)
<b>Detection Radius:</b>	100% (3m)    100% (8m) 50% (2m)      50% (6m)
<b>Hold Time:</b>	5s / 5min / 10min / 30min
<b>Stand-by DIM Level:</b>	10% / 30%
<b>Detection Motion Speed:</b>	1m/s ≥ 3m
<b>Daylight Sensor:</b>	30Lux / 50Lux / 100Lux / Disable

### DIMENSIONS

