


TRIPROOF

TRIPROOF60W15-TRI

SAP CODE: 2001170




1500mm, 60W, Tritone, rugged indoor/outdoor LED batten

A robust and powerful outdoor/indoor IK08 vandal resistant LED batten with Tritone switchable colour temperature.

Accessories
SUSPENSION KIT



Photometric Diagram



Unit: cd
- C0/180 110.0deg
- C90/270 110.0deg

KEY INFORMATION

Lumen Output	5600 / 6000 / 5700lm
Input Power	60W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	COMING SOON

PHOTOMETRIC

Efficacy	93 / 100 / 95lm/W
LED	SMD
CCT	4000 / 5000 / 6500K
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	20-57VDC
Power Factor	>0.9
LED Input Current (nominal)	1050mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Bracket
Connection Type	Terminal Block PA14
Total Weight	3.5kg
Dimensions	1515x116x74mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1
Food Grade Approval	HACCP