

# VISTA EVO

**VISTA-EV06-EM**  
SAP CODE: 2002347


VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

## APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations



## PHOTOMETRIC DIAGRAM



Unit: cd  
 - C0/180 140.9deg  
 - C90/270 109.2deg

Photometric diagram shown is for 4000K output.

## KEY INFORMATION

Power	20 W
Lumen Output	2200 / 2300 / 2200 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL 9003
IP Rating	IP20
IK Rating	Not Applicable
Operating Ambient Temp.	0 to 40°C
Connection Type	PA14 Terminals
Driver	Integrated
Warranty	5 yrs

## PHOTOMETRIC

Efficacy	110 / 115 / 110 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 30
Beam Angle	120°
Flicker-Free	Yes
Lifespan	>50,000hrs @ Ta 25°C (L80)

## ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Electrical Classification	Class I
Power Charging	Not Applicable
Power Standby	Not Applicable
Surge Protection	Overload / Short Circuit

## EMERGENCY INFORMATION

Test Type	Not Applicable
Battery Type	Not Applicable
Recharge Time	Not Applicable
Discharge Time	Not Applicable
Emergency Classification	N/A