

VISTA EVO


VISTA-EV06
SAP CODE: 2002346

VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations

PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 140.4deg
 - C90/270 109.3deg
 Photometric diagram shown is for 4000K output.



KEY INFORMATION

| | |
|-------------------------|--|
| Power | 10 / 13 / 17 / 20 W |
| Lumen Output | 10 W: 1100 / 1150 / 1100 lm 13 W: 1430 / 1495 / 1430 lm 17 W: 1870 / 1955 / 1870 lm 20 W: 2200 / 2300 / 2200 lm |
| Mounting Type | Surface Mount |
| Dimming Type | Non-Dimmable |
| Fascia Colour | White RAL 9003 |
| IP Rating | IP20 |
| IK Rating | Not Applicable |
| Operating Ambient Temp. | -20 to 45°C |
| Connection Type | PA14 Terminals |
| Driver | Integrated |
| Warranty | 5 yrs |

PHOTOMETRIC

| | |
|--------------|--|
| Efficacy | 10 W: 110 / 115 / 110 lm/W 13 W: 110 / 115 / 110 lm/W 17 W: 110 / 115 / 110 lm/W 20 W: 110 / 121 / 110 lm/W |
| CCT | 4000 / 4700 / 5700 K |
| CRI | > 80 |
| SDCM | < 5 |
| UGR | < 30 |
| Beam Angle | 120° |
| Flicker-Free | Yes |
| Lifespan | >50,000hrs @ Ta 25°C (L80) |

ELECTRICAL

| | |
|---------------------------|--------------------------|
| Input Voltage | 220-240Vac, 50/60Hz |
| Power Factor | > 0.9 |
| Electrical Classification | Class I |
| Surge Protection | Overload / Short Circuit |

OTHERS

| | |
|-------------------------|----------------------|
| Body Material | Steel |
| Diffuser Material | Polycarbonate (Opal) |
| Cable Entry | Rear |
| Rebate Scheme Approvals | Not Applicable |
| HACCP Approval | No |
| Weight | 0.72 kg |
| Dimensions | 605 x 65 mm |