

# VISTA EVO

**VISTA-EV12-EM-BK**


SAP CODE: 2002349

VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

## APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations

## PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 139.2deg  
— C90/270 110.4deg

Photometric diagram shown is for 4000K output.



## KEY INFORMATION

|                         |  |
|-------------------------|--|
| Power                   | 20 W<br>40 W                                   |
| Lumen Output            | 2200 / 2300 / 2200 lm<br>4400 / 4600 / 4400 lm |
| Mounting Type           | Surface Mount                                  |
| Dimming Type            | Non-Dimmable                                   |
| Fascia Colour           | Black  |
| IP Rating               | IP20   |
| IK Rating               | Not Applicable                                 |
| Operating Ambient Temp. | 0 to 40°C                                      |
| Connection Type         | PA14 Terminals                                 |
| Driver                  | Integrated                                     |
| Warranty                | 5 yrs  |

## PHOTOMETRIC

|              |  |
|--------------|--|
| Efficacy     | 96 / 105 / 96 lm/W<br>102 / 110 / 102 lm/W |
| CCT          | 4000 / 4700 / 5700 K                       |
| CRI          | > 80                                       |
| SDCM         | < 5  |
| UGR          | < 30                                       |
| Beam Angle   | 120°                                       |
| Flicker-Free | Yes  |
| Lifespan     | >50,000hrs @ Ta 25°C (L80)                 |

## ELECTRICAL

|                           |                          |
|---------------------------|--------------------------|
| Input Voltage             | 220-240Vac, 50/60Hz      |
| Electrical Classification | Class I                  |
| Power Charging            | 1.6 W                    |
| Power Standby             | 3.2 W                    |
| Surge Protection          | Overload / Short Circuit |

## EMERGENCY INFORMATION

|                          |              |
|--------------------------|--------------|
| Test Type                | Self-Test    |
| Battery Type             | LiFePO4 3.2V |
| Recharge Time            | 16 hr        |
| Discharge Time           | 1.5 hr       |
| Emergency Classification | N/A          |