

# VISTA EVO


**VISTA-EV12-EM**  
SAP CODE: 2002349

VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

## APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations

## PHOTOMETRIC DIAGRAM



Unit: cd  
 - C0/180 139.2deg  
 - C90/270 110.4deg

Photometric diagram shown is for 4000K output.



## KEY INFORMATION

Power	20 W 40 W
Lumen Output	2200 / 2300 / 2200 lm 4400 / 4600 / 4400 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL 9003
IP Rating	IP20
IK Rating	Not Applicable
Operating Ambient Temp.	0 to 40°C
Connection Type	PA14 Terminals
Driver	Integrated
Warranty	5 yrs

## PHOTOMETRIC

Efficacy	96 / 105 / 96 lm/W 102 / 110 / 102 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 30
Beam Angle	120°
Flicker-Free	Yes
Lifespan	>50,000hrs @ Ta 25°C (L80)

## ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Electrical Classification	Class I
Power Charging	1.6 W
Power Standby	3.2 W
Surge Protection	Overload / Short Circuit

## EMERGENCY INFORMATION

Test Type	Self-Test
Battery Type	LiFePO4 3.2V
Recharge Time	16 hr
Discharge Time	1.5 hr
Emergency Classification	C0:D63/C90:D40