

VISTA EVO

VISTA-EV12-MS
SAP CODE: 2002350

VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint back packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.

APPLICATIONS


Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations

INTELLISENSOR

Sensor Type	Microwave Motion Sensor
Detection Angle	150°
Mounting Height	3 - 6m (Max)
Detection Radius	Ceiling Mounting @ 3m = 2.5-4m Wall Mounting @ 2m = 3-5m
Hold Time	3s/5s/3min/10min
Stand-by DIM Level	20/30%
Detection Motion Speed	0.3m/s - 1m/s
Daylight Sensor	15 / 50 / 150 Lux / Disable



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 139.0deg
— C90/270 109.6deg

Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	20 W 40 W
Lumen Output	20 W: 2200 / 2300 / 2200 lm 40 W: 4400 / 4600 / 4400 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL 9003
IP Rating	IP20
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA14 Terminals
Driver	Integrated
Warranty	5 yrs

PHOTOMETRIC

Efficacy	20 W: 96 / 105 / 96 lm/W 40 W: 102 / 110 / 102 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 30
Beam Angle	120°
Flicker-Free	Yes
Lifespan	>50,000hrs @ Ta 25°C (L80)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Steel
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Rear
Rebate Scheme Approvals	Not Applicable
HACCP Approval	No
Weight	1.42 kg
Dimensions	1200 x 64 mm