

# VISTA HERO

VISTA-HR12


SAP CODE: 2001940

## Conventional and elegant.

VISTA HERO is a conventional but elegant wide body (125mm) batten suitable for either new installations or retrofit. It offers both Intellisensor (MS) and emergency (EM) versions.



### PHOTOMETRIC DIAGRAM



Unit: cd  
C0/180 113.3deg  
C90/270 134.2deg

Photometric diagram shown is for 4000K output.

#### MECHANICAL

IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Dimensions (LxW)	1230 x 125mm
Dimensions (H)	67mm
Weight	1.5kg
Mounting Type	Surface Mount
Cutout	N/A
Body Material	Steel
Diffuser Material	Polycarbonate
Product Colour	White
Operating Ambient Temperature	-20 to 45°C
Connection Type	PA12 Terminals

#### ELECTRICAL

Wattage	20/40W
Lumen Output	40: 4000 (4K), 4180 (4.7K), 4000 (5K) 20W: 2100 (4K), 2180 (4.7K), 2100 (5K)
Efficacy	Up to 110 lm/W
Input Voltage	220-240Vac, 50/60Hz
Surge Protection	Overload / Short Circuit
Power Factor	>0.95
Electrical Classification	Class 1
Flicker Free	Yes
Driver	Integral
Dimming Method	Non-Dimmable
Smart	KASTA Compatible
Lifespan	>50,000hrs @ Ta 25°C (L70)

#### OPTICAL

CCT	4000K/4700K/5000K
CRI	> 80
UGR	N/A
Beam Angle	120°
UWL	N/A
SDCM	< 5

#### OTHER

Warranty	5 yrs
Government Scheme Approval	N/A
HACCP Approved	Yes