



VISTA


VISTA12-SS
SAP CODE: 2002232

Simple, efficient and flexible.

VISTA, a household name synonymous for quality, when it comes to LED battens. VISTA covers a huge range of applications and is the perfect LED replacement for conventional predecessors. Smart technology such as sensors provide energy savings while Tritone and power switchable technology reduces complexity for the customer.

This model is power switchable, tritone selectable, and features an Intellisensor for automatic standby dimming.

PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 110.0deg
 - C90/270 110.0deg

POWER/LUMEN SETTINGS

POWER	LUMENS	EFFICACY	CCT
18W	2160 lm	120 lm/W	4000K
	2200 lm	120 lm/W	5000K
	2160 lm	120 lm/W	6500K
36W	4000 lm	110 lm/W	4000K
	4200 lm	115 lm/W	5000K
	4000 lm	110 lm/W	6500K

SPECIFICATIONS

Total Weight:	2.00kg
Dimensions:	1221 x 84 x 70mm
Body Material:	SPCC Steel
Diffuser Material:	Polycarbonate (Opal)
Body colour:	White
IP Rating:	IP20
IK Rating:	IK08
Beam Angle:	120°
CRI:	>80
SDCM:	<5
Driver:	Integral
Power Connection:	PA14 Terminals
Input:	220-240V, 50/60Hz
Electrical Classification:	Class 1
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-30 to 45°C
Smart:	KASTA Compatible
Dimming:	Non-Dimmable

INTELLISENSOR

Sensor Type:	Microwave Motion Sensor
Detection Angle:	150°
Mounting Height:	3m 6m (max)
Detection Radius:	100% (3m) 100% (8m) 50% (2m) 50% (6m)
Hold Time:	5s / 5min / 10min / 30min
Stand-by DIM Level:	10% / 30%
Detection Motion Speed:	1m/s ≥ 3m
Daylight Sensor:	30Lux / 50Lux / 100Lux / Disable

DIMENSIONS

