



VISTA

VISTA20/40W12-TRI

SAP CODE: 2001161

Simple, efficient and flexible.

When it comes to batten lighting, VISTA is a familiar name that relates to excellence. VISTA is the universal batten lighting to suit both residential and business environments alike for any application whether it is home storage areas or commercial kitchens. The range is further strengthened with optional emergency or sensor models available.

APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Manufacturing Facilities, Indoor Recreation, General Industrial, Storage Rooms, Kitchen / Food Prep

DIMENSION DIAGRAMS




Disclaimer

NOTE1; SDCM values based on 4K/5.7K CCT

NOTE2; Refer to the installation instructions supplied in the product packaging for the correct and accurate guidance.



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 132.3deg

— C90/270 113.2deg

Photometric diagram shown is for 4700K output.

KEY INFORMATION

Power	20/24/29/34/40 W
Lumen Output	20W: 2609/2742/2657 lm 24W: 3204/3415/3277 lm 29W: 3795/4070/3868 lm 34W: 4255/4623/4368 lm 40W: 4832/5298/4983 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	WHITE W002
IP Rating	IP20
IK Rating	Not applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA14 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	20W: 145/156/146 lm/W 24W: 140/154/141 lm/W 29W: 135/150/135 lm/W 34W: 130/147/130 lm/W 40W: 125/143/125 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	≤5
UGR	> 25
Beam Angle	120°
Flicker-Free	Yes
Projected Lifespan	>72,000hrs @ 40°C (L80)

ELECTRICAL

Input Voltage	220-240Vac 50/60HZ
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	SPCC steel
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Both ends; Rear
Rebate Scheme Approvals	IPART; VEU; REPS;
HACCP Approval	Yes
Weight	2.0 kg
Dimensions	1223 x 84 x 70mm