



VISTA

Indoor Battens

Simple, efficient and flexible.

VISTA, a household name synonymous for quality, when it comes to LED battens. With an extensive range including emergency versions, VISTA covers a huge range of applications and is the perfect LED replacement for conventional predecessors. Smart technology such as sensors provide energy savings, Tritone and power switchable technology reduces complexity for the customer and self-test Emergency automates the EM testing process.

Features

- Tritone colour selectable
- Power switchable
- HACCP approved
- Easy terminal block access
- Extensive range
- Self-test Emergency version
- Sensor version
- Flicker Free
- Improved lumen efficacy

Benefits

- Provides the choice of light hues from a single luminaire;
- Adjust the light to suit the requirements;
- Suitable for food manufacturing;
- Quick and easy installation;
- Covering a huge range of applications;
- Automatic testing reduces maintenance effort;
- Supports power conservation;
- Increase productivity and lowers eye strain;
- More light output using less energy;



Nominal Length 600mm

POWER	LUMENS	EFFICACY	CCT	DIMENSION	WEIGHT	SAP CODE	PRODUCT CODE
15 W	1874 / 2015 / 1928 lm	128 / 142 / 128 lm/W	4000 / 4700 / 5700 K	615 x 84 x 70 mm	1.00 kg	2001157	VISTA20W06-TRI
16 W	2048 / 2219 / 2108 lm	125 / 140 / 125 lm/W			1.27 kg	2001158	VISTA20W06-TRI-EM
18 W	2202 / 2402 / 2270 lm	122 / 139 / 122 lm/W					
20 W	2390 / 2599 / 2435 lm	121 / 137 / 119 lm/W					

Nominal Length 1200mm

POWER	LUMENS	EFFICACY	CCT	DIMENSION	WEIGHT	SAP CODE	PRODUCT CODE
20 W	2608 / 2741 / 2656 lm	144 / 156 / 145 lm/W	4000 / 4700 / 5700 K	1221 x 84 x 70 mm	1.89 kg	2001161	VISTA20/40W12-TRI
24 W	3204 / 3414 / 3276 lm	139 / 153 / 140 lm/W					
29 W	3795 / 4070 / 3868 lm	135 / 150 / 135 lm/W			2.15 kg	2001063	VISTA20/40W12-TRI-EM
34 W	4254 / 4623 / 4368 lm	129 / 146 / 130 lm/W					
40 W	4831 / 5297 / 4983 lm	124 / 142 / 125 lm/W					
20 W	2644 / 2748 / 2657 lm	140 / 150 / 141 lm/W			1.95 kg	2002232	VISTA12-SS
26 W	3466 / 3627 / 3466 lm	134 / 147 / 135 lm/W					
35 W	4408 / 4676 / 4404 lm	126 / 141 / 126 lm/W			2.24 kg	2001065	VISTA40W12-TRI-SS-EM
40 W	4860 / 5202 / 4861 lm	121 / 137 / 121 lm/W					

Nominal Length 1500mm

POWER	LUMENS	EFFICACY	CCT	DIMENSION	WEIGHT	SAP CODE	PRODUCT CODE
28 W	3855 / 4084 / 3943 lm	143 / 156 / 143 lm/W	4000 / 4700 / 5700 K	1523 x 84 x 70 mm	2.9 kg	2001162	VISTA60W15-TRI
36 W	4821 / 5156 / 4897 lm	136 / 150 / 134 lm/W			3.0 kg	2001163	VISTA60W15-TRI-EM
44 W	5617 / 6108 / 5757 lm	129 / 146 / 128 lm/W					
51 W	6268 / 6851 / 6362 lm	124 / 142 / 122 lm/W					
60 W	6973 / 7698 / 7085 lm	119 / 137 / 116 lm/W					

SPECIFICATIONS

Body Material:	SPCC steel
Diffuser Material:	Polycarbonate (Opal)
Body colour:	White
IP Rating:	IP20
Beam Angle:	120°
CRI:	> 80
SDCM:	< 5
Operating Temperature:	-20 to 45°C
	0 to 40°C (EM Model)

Driver:	Integral
Connection Type:	PA14 Terminals
Input:	220-240Va.c. 50/60Hz
Electrical Classification:	Class I
Power Factor:	> 0.9
Protection:	Overload / Short Circuit
Lifespan:	72,000hrs @Ta25° (L80)*
Smart:	KASTA Compatible
Dimming:	Non-Dimmable

* Based on rated LED design life
** +3W while Battery charging

APPLICATIONS

- Kitchen / Food Prep
- Garage
- Shed
- Office
- Education Facilities
- Store Rooms
- Storage Facilities
- Workshops
- Manufacturing Facilities
- Indoor Recreation
- General Industrial

DIMENSIONS (mm)

