

VIVA EVO

VIVA-EVO-FL SAP CODE: 2002399


Simple and Effective

VIVA EVO trade pack is Haneco's simple solution for an effective and economical residential downlight for tradespeople. With the visual attributes and performance akin to the popular VIVA, it is the ideal solution for simple and effective lighting.

APPLICATIONS


Bedrooms, Lounge Room, Dining Area, Laundry, Butler Pantry, Hallways, Entrance, Staircase, Bathrooms, Ensuite, Theatre Rooms, Games Rooms, Function Areas, Hotel Rooms, Kitchen / Food Prep

DIMENSION DIAGRAMS





PHOTOMETRIC DIAGRAM



Unit: cd -- C0/180,103.3 -- C90/270,99.9

Photometric diagram shown is for 4200 K output.

KEY INFORMATION		
Power	8 W	
Lumen Output	720 / 800 / 720 lm	
Cutout Size	Ø 90 mm	
Mounting Type	Recessed	
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)	
Body Colour	White	
IP Rating	IP44 F - IP20 B	
IC Rating	IC-4	
Operating Ambient Temp.	-20 to 40°C	
Connection Type	600mm Flex & Plug	
Driver	Integral	
Warranty	5 yrs	

PHOTOMETRIC		
Efficacy	90 / 100 / 90 lm/W	
CCT	3000 / 4200 / 5700 K	
CRI	> 80	
SDCM	< 7	
UGR	> 25	
Beam Angle	100°	
Flicker-Free	No	
Projected Lifespan	>47,000hrs@Ta25°C(L70)	

ELECTRICAL		
Input Voltage	220-240Vac 50/60Hz	
Power Factor	> 0.9	
Electrical Classification	Class II	
Surge Protection	Overload / Short Circuit	

	Surge Protection	Overload / Short Circuit
	OTHERS	
	Adjustable Angle	Not applicable
	Body Material	Polycarbonate
	Diffuser Material	Polycarbonate (Opal)
	Rebate Scheme Approvals	Not Applicable
	Weight	0.2 kg
	Dimensions	Ø113 x 62 mm