





# VIVA 115

**VIVA-FL-TRI**  
SAP CODE: 2001847

## APPLICATIONS



### MECHANICAL

IP Rating	IP44
IK Rating	Not applicable
Dimensions	Ø113mm
Weight	0.2kg
Mounting Type	Recessed
Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Body Colour	White
Operating Temperature	
Driver	Integral
Power Connection	1m Flex & Plug

### ELECTRICAL

Wattage	8W
Lumen Output	800/850/800 lm
Efficacy	100/106/100 lm/W
Input Voltage	220-240Vac 50/60Hz
Surge Protection	Overload / Short Circuit
Power Factor	>0.9
Electrical Classification	Class II
Dimming	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Smart	KASTA Compatible
Lifespan	>50,000hrs@Ta25°C(L70)
Protection	Overload / Short Circuit

### OPTICAL

CCT	3000K/4200K/5700K
CRI	> 80
UGR	< 19
Beam Angle	100°
UWL	Not applicable
SDCM	&lt;5 

### OTHER

Warranty	5 yrs
Government Scheme Approval	IPART; VEU; REPS; HEER;




# VIVA 115

**VIVA-FL-TRI**  
SAP CODE: 2001847

## Conventional and Versatile

Discover the radiance of VIVA, a range of versatile yet economical downlights complete with the choice of flush or recessed opal diffusers. Designed to be adaptable within the everyday home, it is suited for wet rooms such as bathrooms and laundries courtesy of the IP44 and IC-4 ratings, ensuring its suitability for humid environments without

### DIMENSIONS



### ACCESSORIES