



VIVA^{LP}

VIVA-LP

SAP CODE: 2002396



A compact and complete luminaire.

VIVA LP from Haneco has become the new benchmark for conventional home lighting systems. The VIVA LP features tritone colour technology, dimming capabilities, and high efficacy outputs all wrapped in a small housing that can meet any installation requirement, helping it to maintain its status as the industry standard for home lighting.

APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Butler Pantry, Hallways, Entrance, Staircase, Bathrooms, Ensuite, Theatre Rooms, Games Rooms, Function Areas, Hotel Rooms, Kitchen / Food Prep

DIMENSION DIAGRAMS



Disclaimer

NOTE 1: SDCM values measured on 3K/5.7K CCT


NOTE 2: CRI value measured on 5.7K CCT

NOTE 3: Inside roof cavity assumes 10mm plasterboard thickness

haneco.com.au

Specification subject to change without prior notice. Last updated 18/07/2024

PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180,109.4deg
— C90/270,107.deg

Photometric diagram shown is for 4000K output.



KEY INFORMATION

Power	8 W
Lumen Output	800 / 850 / 800 lm
Cutout Size	90 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP44
IC Rating	IC-4
Operating Ambient Temp.	-20 to 40°C
Connection Type	1m Flex & Plug
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	100 / 106 / 100 lm/W
CCT	3000 / 4200 / 5700 K
CRI	> 85
SDCM	< 3
UGR	< 37
Beam Angle	100°
Flicker-Free	Yes
Projected Lifespan	>102,000hrs@Ta25°C(L70)

ELECTRICAL

Input Voltage	220-240Vac 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Adjustable Angle	Not applicable
Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Rebate Scheme Approvals	Not Applicable
Weight	0.2 kg
Dimensions	Ø113 x 38 mm (25mm Inside Roof Cavity)