



VIVA SEN

VIVA-SEN

SAP CODE: 2002398

Motion controlled lighting.

Haneco's VIVA SEN is made to satisfy the demands of a simpler lifestyle. The VIVA SEN has the standard features of a practical downlight, such as tritone colour and IC-4 approval, but it additionally contains a PIR sensor that, without the need for additional hardware, turns on the light automatically when movement is detected in the room.



APPLICATIONS

Butler Pantry, Walk-in Wardrobes, Storage Rooms, Laundry, Entrance, Function Areas


SENSOR INFORMATION

Sensor Type	PIR
Detection Angle	360°
Detection Radius	3 m
Daylight Threshold	8-20 lux
Hold Time	30±5 s

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd

— C0/180 81.8deg

— C90/270 80.5deg

Photometric diagram shown is for 4000K output.



KEY INFORMATION

Power	9 W
Lumen Output	700 / 800 / 750 lm
Cutout Size	92 mm
Mounting Type	Recessed
Dimming Type	Non-Dimmable
Body Colour	White
IP Rating	IP20
IC Rating	IC-4
Operating Ambient Temp.	-10 to 45°C
Connection Type	900mm Flex & Plug
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	77 / 94 / 83 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 30
Beam Angle	80°
Flicker-Free	Yes
Projected Lifespan	>30,000hrs@Ta25°C(L70)

ELECTRICAL

Input Voltage	220-240Vac 50/60Hz
Power Factor	> 0.5
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Adjustable Angle	Not applicable
Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Rebate Scheme Approvals	Not Applicable
Weight	0.2 kg
Dimensions	Ø110 x 68 mm