



# VIVA 145

**VIVA145-TRI**  
SAP CODE: 2001103

## Flush, seamless design.

With its clean flush design and wide range of features, VIVA 145 is a proven performer and has established itself as the customer's choice.

### APPLICATIONS

Bathrooms, Boardroom / Meeting Rooms, Dining Area, Food Courts, Function Areas, Medical Facilities, Hotel Common Areas, Offices, Restaurants / Cafes, Staircase, Storage Rooms, Kitchen / Food Prep

### DIMENSION DIAGRAMS



### KEY INFORMATION

Power	14 W
Lumen Output	1240 / 1260 / 1160 lm
Cutout Size	Ø 125 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP44
IC Rating	Non-IC
Operating Ambient Temp.	-20 to 40°C
Connection Type	1.2m Flex & Plug
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	89 / 90 / 83 lm/W
CCT	3000 / 4200 / 5700 K
CRI	> 80
SDCM	< 3
UGR	< 25
Beam Angle	90°
Flicker-Free	No
Projected Lifespan	>50,000hrs @Ta25°C(L70)

### ELECTRICAL

Input Voltage	220-240Vac, 50-60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

### OTHERS

Adjustable Angle	Not Applicable
Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Clear)
Rebate Scheme Approvals	VEU, IPART, REES / REPS
Weight	0.29 kg
Dimensions	Ø145 x 65 mm