


# VISTA<sup>LINE</sup>

(formerly VISTA<sup>LITE</sup>)

VSL20W06-TRI

SAP CODE: 2001630




## 20W Tritone indoor LED batten

A diffused appearance LED batten with a choice of 3 colour temperatures.



Photometric Diagram



Unit: cd  
 - C0/180 120.0deg  
 - C90/270 120.0deg

### KEY INFORMATION

Lumen Output	2150 / 2260 / 2130lm
Input Power	20W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	IPART Approved

### PHOTOMETRIC

Efficacy	108 / 113 / 107lm/W
LED	SMD
CCT	4000 / 4700 / 5700K
CRI	>80
Beam Angle	120°

### ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	40VDC
Power Factor	>0.9
LED Input Current (nominal)	500mA
Useful life @Ta25° (L70)	50,000hr

### CONSTRUCTION

Housing	Powder Coated Steel
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block
Total Weight	0.9kg
Dimensions	615 x 68 x 68mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1