




DONUT

DONUT25W-WH

SAP CODE: 2002248




Unique, smooth and functional.

DONUT is a decorative wall and ceiling luminaire with unique, smooth and light aesthetics. A magnet held centre plate and keyholes at the back ensure installation is a breeze.



Photometric Diagram



Unit: cd
 - C0/180 104.4deg
 - C90/270 104.3deg

KEY INFORMATION

Lumen Output	2200lm
Input Power	25W
Install	SURFACE MOUNT
Warranty	5yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A

PHOTOMETRIC

Efficacy	88lm/W
LED	SMD
CCT	3000 / 4000K
CRI	>80
Beam Angle	100°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	21-42V DC
Power Factor	0.95
LED Input Current (nominal)	600mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Powder Coated Steel
Diffuser Material	Polycarbonate (Opal)
Body Colour	White: RAL 9016
Connection Type	Terminal Block
Total Weight	1.3kg
Dimensions	Ø351 x 71.5mm
Operating Ambient Temp.	-20 to 40°C
Electrical Classification	Class 2