



LUME

Emergency Luminaires

A reliable path to building safety.

LUME is a sleek, emergency luminaire suitable for a large variety of applications, due to its recessed and surface mounting options. Using reliable lithium iron phosphate (LiFePO₄) battery technology, this state-of-the-art product ensures low maintenance and energy efficiency. Compliant to AS/NZS 2293.3, offering D40/D63 emergency classification.

Features

- D40 or D63 emergency classification
- Simple test button
- IC-4 Rating allows covering with building insulation
- LiFePO₄ battery compliant with AS2293.3
- More than 2 hours discharge time
- Available in surface mount and black or white finish

Benefits

- Optimised product spacings
- Easy maintenance
- Simple and quick installation
- Peace of mind for end user
- Ensured and guaranteed safety
- Suitable for a wide range of applications



Product Overview

POWER (Standby)	POWER (Charging)	DISCHARGE TIME	RECHARGE TIME	LUMENS	CCT	EMERGENCY CLASSIFICATION	CUTOUT	SAP CODE	PRODUCT CODE
0.5W	1.5W	>2 hours	16 hours	100lm	5700K	D40	Ø90/110mm Ø90/110mm	2002009 2002176	LUME1WD40 LUME1WD40-BK
0.5W	4W	>2 hours	16 hours	340lm	5700K	D63	Ø90/110mm Ø90/110mm	2001853 2001872	LUME3WD63 LUME3WD63-BK
0.5W	4W	>2 hours	16 hours	340lm	5700K	D63	- -	2001869 2001873	LUME3WD63-SM LUME3WD63-SM-BK

SM = Surface Mount **BK** = Black

SPECIFICATIONS

Type:	Non-Maintained	Driver:	Integral
Body Material:	Polycarbonate	Power Lead:	1.5m Flex & Plug
Diffuser Material:	Polycarbonate (Clear)	Input:	220-240V, 50/60Hz
Fascia Colour:	White Black	Electrical Classification:	Class 2
IP Rating:	IP40	Battery Type:	LiFePO4 3.2V 3.3Ah
IC Rating:	IC-4 (ta 25°C)	Charger Operation:	Continuous
AS/NZS Standards:	60598 / 2293.3	Battery Test Button:	Manual
Beam Angle:	150°	Lifespan:	>50,000hrs @Ta25°C (L70)
CRI:	>80	Weight:	0.3kg
		Operating Ambient Temperature:	0 to 40°C

APPLICATIONS

Office Buildings
Shopping Centres
Car Parks
Sporting Venues
Schools
Hospitals
Hotels
Bars and Restaurants
Industrial Facilities
Warehouses
Foyers and Hallways
Multi-Residential

ACCESSORIES

Ø140mm Adaptor
(Ø110mm Cut Out)
(included)



Suspension Kit:
SM-ENC-SUSKIT
(SAP 2001871)
(Connects to Surface Mount only)

Exit and Emergency



White



Black




White (Surface Mount)




Black (Surface Mount)


DIMENSIONS



LUME1WD40



LUME3WD63



LUME3WD63-SM

FIND OUT MORE:

