



# TRIM

## Residential Downlights



**DIM**  
Phase Cut  
Dimming



**IP20**  
Ingress  
Protection  
Rating



**UGR<19**  
Beam  
Angle



**IC-4**  
Covered &  
Abutted



**50,000hr**  
Expected  
Lifetime



**5yr**  
Warranty

### Target feature walls and spaces.

TRIM series is a range of low glare LED downlights boasting an ultra-slim trim design. With single lamp fixed, single wall washer or double lamp adjustable, it adds great value to apartment and hospitality projects.

### Features

- Ultra-slim trim
- Single fixed, wall washer and adjustable twin lamp
- Deep recessed lens
- Robust diecast aluminium construction
- Complete with flex and plug

### Benefits

- Blends in with the ceiling
- Enhanced design freedom
- Extra low glare
- Improved thermal characteristics
- Quick and easy installation

FEATURE	POWER	LUMENS	EFFICACY	CCT	CUTOUT	WEIGHT	SAP CODE	PRODUCT CODE
Single	11W	1050 lm	95 lm/W	4000K	Ø92mm	0.24kg	2002042	<b>TRIM11W4K50D</b>
		980 lm	89 lm/W	3000K			2002041	<b>TRIM11W3K50D</b>
Single (Wall Washer)	11W	930 lm	85 lm/W	3000K	Ø92mm	0.27kg	2002043	<b>TRIM11W3K50DWW</b>
Double	22W (2x11W)	1790 lm	81 lm/W	3000K	75 x 153mm	0.55kg	2002044	<b>TRIM22W3K50D</b>

### SPECIFICATIONS

<b>Body Material:</b>	Aluminium	<b>Driver:</b>	Remote
<b>Diffuser Material:</b>	Polycarbonate (Clear)	<b>Power Lead:</b>	1.2m Flex & Plug
<b>Fascia colour:</b>	White: W110	<b>Input:</b>	220-240V, 50/60Hz
<b>IP Rating:</b>	Front: IP20 Body: IP20	<b>Electrical Classification:</b>	Class 2
<b>IC Rating:</b>	IC-4 (ta 25°C)	<b>Power Factor:</b>	>0.9
<b>Beam Angle:</b>	24° (19° with Pin-Hole)	<b>Protection:</b>	Overload / Short Circuit
<b>CRI:</b>	>80 (>90 option)	<b>Lifespan:</b>	>50,000hrs @Ta25°C (L70)
<b>UGR:</b>	<19	<b>Operating Ambient Temperature:</b>	-20 to 45°C
<b>SDCM:</b>	<5 (<3 option)	<b>Smart:</b>	KASTA Compatible
		<b>Dimming:</b>	Phase-Cut Dimmable (Trailing Edge) DALI Dimmable Models Available. See Page 212.

### APPLICATIONS

Living Rooms  
Hotels  
Meeting rooms  
Hallways



Single







Single (Wall Washer)




Double

### DIMENSIONS




Remote Driver 110x40x22mm

**TRIM11W\*K50D**



Remote Driver 110x40x22mm

**TRIM11W3K50DWW**



Remote Driver 120x45x28mm

**TRIM22W3K50D**

FIND OUT MORE:

