

UNO

Indoor Battens

Sleek and stylish.

UNO is a stylish and minimalistic aluminium profile luminaire, offering outstanding performance and design flexibility for architecturally demanding applications.



Features

- Tritone selectable
- Surface mount and suspension kit included
- Slim appearance with elegant opal diffuser
- Available in 900, 1200 and 1500mm
- Powder coated aluminium extrusion

Benefits

- Reduced SKUs and inventory levels
- Enhanced application options
- Appealing aesthetics
- Enhanced design freedom
- High quality feel

Product Overview

POWER	LUMENS	EFFICACY	CCT	DIMENSIONS	WEIGHT	FINISH	SAP CODE	PRODUCT CODE
30W	2400 lm	80 lm/W	3000K	907 x 85 x 50mm	1.25kg	Black White	2001972 2001969	UNO30W09BK UNO30W09WH
	2500 lm	83 lm/W	4000K					
	2400 lm	80 lm/W	5000K					
40W	3500 lm	80 lm/W	3000K	1204 x 85 x 50mm	1.80kg	Black White	2001973 2001970	UNO40W12BK UNO40W12WH
	3700 lm	93 lm/W	4000K					
	3400 lm	85 lm/W	5000K					
50W	4150 lm	83 lm/W	3000K	1500 x 85 x 50mm	2.20kg	Black White	2001974 2001971	UNO50W15BK UNO50W15WH
	4250 lm	85 lm/W	4000K					
	4200 lm	84 lm/W	5000K					

SPECIFICATIONS

Body Material: Aluminium	Driver: Integral
Diffuser Material: Polycarbonate (Opal)	Power Lead: 1.2m Flex & Plug
Body colour: White Black	Input: 220-240V, 50/60Hz
IP Rating: IP40	Electrical Classification: Class 1
Beam Angle: 110°	Power Factor: >0.9
CRI: >80 (>90 option)	Protection: Overload / Short Circuit
SDCM: <5 (<3 option)	Lifespan: >50,000hrs @Ta25°C (L70)
	Operating Ambient Temperature: -20 to 45°C
	Dimming: Non-Dimmable

APPLICATIONS

- Residential
- Office
- Retail
- Museums
- Libraries
- Colleges
- Schools

ACCESSORIES

Suspension Kit
UNO-SUS KIT
(SAP 2002268)



White



Black




Access Panel

DIMENSIONS



UNO30W09



UNO40W12



UNO50W15

FIND OUT MORE:

