


2-Wire Switch Relay Mechanism

KASTA-S350BH-W



FEATURES

- Max. load 350W or 100W motor
- 2-wire connection for easy installation
- Reliable Bluetooth® mesh network connectivity to all your KASTA devices
- 8-way multiway control
- Short press for ON/OFF control
- Over-current protection
- Supports core KASTA functionality control devices, groups, scenes, timers and scheduling
- Suits most Australian wall plates (up to 3)
- Supplied with White button caps (2 x styles)
- iOS and Android app setup and control
- 3 year warranty




SPECIFICATIONS

Power Supply	220-240V a.c. 50Hz
Operating Ambient Temperature	-20 to 40°C
IP Rating	IP20
Thermal Derating	25 to 40°C (350W-190W)
Physical Connection Type	Fly leads
Wiring Connections	Active & Load
LED Load Wattage	15W - 350W*
Multi-gang Derating	2-260W, 3-190W @ 25°C
Housing Material	Polycarbonate (PC)
LED Indicators	Blue
Standards Complied	CoS SAA 183650, AS/NZS 60669.2.1, AS/NZS 60669.1, AS/NZS CISPR 15, AS/NZS 4268

^{*}May require load correct capacitor if less than 15W (supplied in box). Suitable for use with small fan motors <100W (0.5A @ 0.8pF).

DIMENSIONS



CONNECTION

