## Unison<sup>™</sup> Switch Relay Mechanism



Push button switch relay mechanism that clips into standard wall plate

#### **FEATURES**

- Max. load 1440W or 100W motor
- Slim design allows installation up to 6 onto a standard wall plate
- Short press for ON/OFF control
- Over-current protection
- Suits most Australian wall plates
- Supplied with White button cap
- 3 year warranty

CONNECTION


#### MERGINA AND MERGINA AND FUNCTION AND FUNCTION AND MERGINA AND FUNCTION AND MERGINA MERCINA MER


### SPECIFICATIONS

Power Supply	220-240V a.c.
Operating Ambient Temperature	-20 to 40°C
IP Rating	IP20
Thermal Derating	25 to 40°C (1440W-475W)
Physical Connection Type	Fly leads
Wiring Connections	Active, Load & Neutral
LED Load Wattage	15W - 1440W*
Multi-gang Derating	2-1300W, 3-1150W, 4-950W, 5-720W, 6-475W @ 25℃
Housing Material	Polycarbonate (PC)
LED Indicators	Blue
Standards Complied	AS/NZS 60669.2.1, AS/NZS 60669.1, AS/NZS CISPR 15, AS/NZS 4268

\*May require load correct capacitor if less than 15W (supplied in box). Suitable for use with small fan motors <100W (0.5A @ 0.8pF).

#### DIMENSIONS





# 

