HANECO
IDEAS THAT SHINE

LED Strips & Strip Housing

FLEXION 5M KIT

FS12W5MWW-IP65

SAP CODE: 2000595

Photometric Diagram



Unit: cd
– C0/180 115.0deg
– C90/270 115.0deg



3000K, IP65, 12W, 5m flexible, trimmable, LED strip

An LED strip for outdoor use and accent lighting.

Accessories

DIMMABLE DRIVER

KEY INFORMATION

Lumen Output (p/metre)	180lm/m
Lumen Output	900lm
Input Power	2.4W/m
Install	SURFACE/DS TAPE
Dimming	Non-Dimmable
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP65
Rebate Scheme Approvals	N/A
Cut Interval	167mm

PHOTOMETRIC

LED	SMD
Efficacy	15lm/W
CCT	3000K
CRI	>85
Beam Angle	120°

ELECTRICAL

Driver	Remote
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	12VDC
Power Factor	>0.9
LED Input Current (nominal)	1000mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Fixings/Hardware	Self Adhesive Backing & Saddles
Connection Type	1.1m Flex & Plug
Total Weight	0.46kg
Dimensions	10 x 6 x 5000mm
Operating Ambient Temp.	-30 to 55°C
Electrical Classification	Class 2

Specification subject to change without prior notice. Last updated **30/01/2019**